



---

# UHF MICROPHONE MOUNT LEFT-HAND SIDE

---

TLR744009



SUITED TO:

**FORD RANGER/RANGER RAPTOR/  
EVEREST – NEXT GEN SERIES**



## PRE-INSTALLATION



Read through this installation guide before proceeding.



Fitting time is approx. 30 minutes.



Allen Key, Drill  
12 mm Drill bit, Screwdriver,  
Trim removal tool  
Masking tape

### FITTING KIT

QUANTITY	PART
1	TLR744009 –Mount



#### NOTE:


This UHF Microphone Mounting Bracket is designed to mount to the Left-Hand side of the centre console area.

There are mounting holes to accommodate most UHF base plates, along with a 28 x 18mm hole to suit Toyota short switches EG. XRS-RJ45W1 (RJ45 Pass-Through Adapter – Type 1).



## FITTING INSTRUCTIONS

1. Remove the Small Triangle shape trim piece as shown in *Photo 1*. there are 3 clips holding this in place, to remove simply lever or pull the piece of trim out from the console to release.
2. Install the UHF handpiece mount and RJ45 pass-through into the TLR Products mount, Refer to Photo on previous page for example.
3. Carefully use a step drill to create a hole large enough to pass the RJ45 connector through in the bottom surface of the opening shown in *Photo 2*.
4. Route the RJ45 cable up behind the plastic side panel of the centre console and out of the hole previously drilled, connect the cable to the pass-through. *See photo 2*.
5. Feed the excess cable back through the hole and firmly push the TLR Products mount into position until all 3 clips are securely in place to finalise installation



[instagram.com/tlrproducts](https://www.instagram.com/tlrproducts)  
[facebook.com/tlrproducts](https://www.facebook.com/tlrproducts)



[hello@tlrproducts.com.au](mailto:hello@tlrproducts.com.au)  
[www.tlrproducts.com.au](http://www.tlrproducts.com.au)